

► HALEBAS POUSSANT / VANG FITTING



37560230305

2004

CODE	Taille Size	Longueur ouverte Length open	Longueur fermée Length closed	Course mm Course mm	Poussée maxi du ressort (kg) Max spring strength	Réf. fixation/mât Mast attachment	Réf. fixation/bôme Boom attachment	Axe sur mât Pin on mast	Axe sur bôme Pin on boom
37560200005	0	1350	1160	190	0	3521181PF05	35243200164	8	10
37560210105	1	1160	970	190	100	3521181PF15	35243200164	14	14
37560220105	2	1395	1155	240	115	3521181PF15	35243202734/6504	14	14
37560230105	3	1740	1450	290	115	3521181PF15	35243202734/6504	14	14
37560240105	4	2000	1710	290	115	3521181PF15/PF25	35243202734/6504	14	14
37560230205	3	1740	1450	290	230	3521181PF15/PF25	35243202734/6504	14	14
37560240205	4	2000	1710	290	230	3521181PF15/PF25	35243202734/6504	14	14
37560250305	5	2000	1710	290	345	3521181PF25	35243206504	14	14
37560250405	5	2000	1710	290	460	3521181PF25	35243206504	14	14
37560250505	5	2000	1710	290	575	3521181PF25	35243206504	14	14
37560250605	5	2300	2010	290	345	3521181PF25	35243206504	14	14
37560250705	5	2300	2010	290	460	3521181PF25	35243206504	14	14
37560250805	5	2300	2010	290	575	3521181PF25	35243206504	14	14

Livré sans palan ni estrope.

Purchase and bridle not included.

Estrope / Bridle

Réf.	Taille HB / Size					
	0	1	2	3	4	5
43505061600 Lg 1,6 m	X	X	X			
43505062000 Lg 2 m				X		
43505062200 Lg 2,2 m					X	*

* Nous consulter / On request.

Bôme Boom	Ferrure de halebas rigide Rigid vang attachment	Largeur Width	Épaisseur Thickness
F36	35243200164	23 mm	1,5 mm
F60	35243200164		
F125	35243202734	26,5 mm	2,5 mm
F220	35243202734		
F550	35243206504	30 mm	4 mm
F810	35243206504		
F1700	35243206504		
F3400	35243206504		